



# ZEBRA AN440 RFID ANTENNA

## HIGH PERFORMANCE FOR HIGH THROUGHPUT ENVIRONMENTS

### LARGE AREA COVERAGE IN NEARLY ANY ENVIRONMENT

Need to keep track of thousands of assets? High product density and heavy traffic across a large area? Get the capacity and range you demand for reliable RFID tag reading with the AN440 high-performance RFID area antenna. A good-looking, rugged general-purpose area antenna, the AN440 is designed to perform exceptionally in all environments, indoors and out. The AN440 RFID Antenna gives you a wide read field and high-speed RF signal conversion, so data capture is fast and accurate, even in expansive, high-demand environments. The AN440 is easy to mount on ceilings and walls, and its rugged white housing is at home in both customer-facing and industrial settings. So you can achieve superior read zones around stockroom shelves, warehouse doorways and dock platforms – anywhere boxes and pallets are moving into and out of your facility.

### HIGHEST PERFORMANCE, MEET LONGEST READ RANGE

The rectangular AN440 antenna is designed to deliver faster, more accurate communication of EPC-compliant passive tag data to your RFID readers. So even in RF-challenging environments, you get longer read ranges and higher levels of performance. Your workflow keeps flowing, your inventory count stays accurate and your productivity can reach new heights. In addition, its dual-element architecture makes the AN440 suitable for bi-static operation. Or it can be used as two separate mono-static antennas in a single package. Deployment with Zebra fixed RFID readers is fast and easy, as the AN440 meets all standard technical requirements for any RFID implementation. So you can get your large-area application off the drawing board and into your production environment, quickly and efficiently.

### END-TO-END LIFECYCLE SUPPORT

No matter what help you might need, we have you covered. Our full suite of services offers ‘from the manufacturer’ expertise throughout the entire lifecycle of your RFID solution — from assessment, commissioning and rollout to ongoing training and day-to-day support. Our RFID Advanced Services provide the assistance you need to architect your solution for your business, processes and environment, ensuring that your pilot or full-scale rollout is designed to deliver peak performance — and maximum benefits. And post deployment, Zebra’s Support Services provide the everyday support you need to keep your RFID solution up and running day in and day out, with service programs that include 24x7 on-site coverage and preventive maintenance visits.

For more information on how the AN440 RFID Reader can benefit your business, please visit us on the web at [www.zebra.com/an440](http://www.zebra.com/an440) or access our global contact directory at [www.zebra.com/contact](http://www.zebra.com/contact)

### FEATURES

- Dual-element, ideal for bi-static operation
- Can be used as two separate mono-static antennas in one package
- Rugged design suitable for industrial applications

### APPLICATIONS

- Ceilings and walls to create superior read zones around shelves
- Doorways and chokepoints where boxes and pallets are moving through
- Portals, outdoor gates and conveyors
- RF-challenging environments

## AN440 RFID ANTENNA SPECIFICATIONS CHART

### PHYSICAL

#### Dimensions

22.6 inches L x 10.2 inches W x 1.32 inches D (575.1 mm L x 259.1 mm W)

### ENVIRONMENTAL

#### Environmental Sealing

IP-67

#### RHOS Compliant

Yes

	x 33.52 mm D)	<b>Storage Temperatures</b>	-40°F to +185°F (-40°C to +85°C)
<b>Connectors</b>	2 x Type N female	<b>Vibration</b>	IEC-68-2-6 (10 to 150 Hz, 05 g, 1 hour in each of two axes) (Random Vibration)
<b>Connector Position</b>	Back	<b>Humidity</b>	MIL-Std 810G, METHOD 507.5, Procedure II - Aggravated
<b>Mounting Bracket</b>	Integrated mounting holes	<b>Warranty</b>	The AN440 is warranted against defects in workmanship and materials for a period of one year (12 months) from date of shipment, provided the product remains unmodified and is operated under normal and proper conditions.
<b>Weight</b>	4.2 lbs (1.9 kg )		
<b>Casing</b>	UV Stable ASA		
<b>Radome Material</b>	UV Stable ASA, White		
<b>OPERATIONAL</b>			
<b>Frequency Range</b>	EU: 865-868MHz; US*: 902-928MHz *AN440 is optimized for US frequency		
<b>Gain</b>	6 dBiL	<b>RECOMMENDED SERVICES</b>	
<b>VSWR (Return Loss)</b>	<1.4 : 1	<b>Support Services</b>	Service from the Start Advance Exchange On-Site System Support
<b>Front to Back Ratio</b>	20 dB	<b>Advanced Services</b>	RFID Design and Deployment Services
<b>Polarization</b>	1 x LHCP / 1 x RHCP		
<b>3db Beam Width</b>	70° in both phases		
<b>Max Power</b>	10 W		
<b>Axial Ratio</b>	1dB typical		
<b>Operating Temperatures</b>	-22°F to +158°F (-30°C to +70°C )		
<b>DC Resistance</b>	DC Grounded		



Part number: SS-AN440.©2015 ZIH Corp. ZEBRA, the Zebra head graphic and Zebra Technologies logo are trademarks of ZIH Corp, registered in many jurisdictions worldwide. All rights reserved. All other trademarks are the property of their respective owners.

**ZEBRA TECHNOLOGIES**